

FICHE TECHNIQUE

Briques de revêtement mural en textile pour sublimer, uniquement, des espaces intérieurs, sur des surfaces verticales. Non adaptées aux pièces humides (salle de bain, cuisine, etc). À installer hors de portée des enfants.

Composition	textiles broyés + liant biosourcé
Dimensions (cm)	~ 20x10 (en moy. : 19,7x9,8)
Épaisseur (cm)	~ 2
Masse volumique (kg/m ³)	500
Surface	poreuse
Coloris	9 coloris catalogue (ou personnalisé)
Motif	3 motifs : uni, terrazzo & dégradé
Finition	vernis facultatif
Coefficient d'absorption acoustique (NF EN ISO 11654)	0,45
Conductivité thermique (W/mK) (NF EN 12667 : 2001)	0,085
Classement FR de réaction au feu (NF P92-501 : 1995)	M2 (M1 sur demande)
Classement EUROCLASS de réaction au feu (NF EN 13501-1 : 2018)	C-s1-d0
Émission de COV	étiquetage français A+
Entretien	aspiration douce tous les 3 à 5 mois
Production	fabriqué à Paris

Cette fiche technique annule et remplace les précédentes. Assurez-vous qu'elle est toujours en vigueur. Toute utilisation ou mise en œuvre des matériaux non conformes aux règles prescrites dans ce document, dégage le fabricant de toute responsabilité, notamment de sa responsabilité solidaire (art.1792-4 du code civil).

FabBRICK®

www.fab-brick.com
contact@fabbrick.fr

Mise à jour 10/2025

DATA SHEET

Textile wall cladding bricks designed to enhance interior spaces only, on vertical surfaces. Not suitable for humid areas (bathrooms, kitchens, etc. Should be installed out of children's reach.

Composition	shredded textiles + bio-based binder
Dimensions (cm)	~ 20x10 (avg. : 19,7x9,8)
Thickness (cm)	~ 2
Volumic mass (kg/m ³)	500
Surface	porous
Color	9 colours catalog (or custom)
Pattern	3 patterns : plain, terrazzo & gradient
Finish	optional varnish
Sound absorption coefficient (NF EN ISO 11654)	0,45
Thermal conductivity (W/mK) (NF EN 12667 : 2001)	0,085
Reaction to fire / French classification (NF P92-501 : 1995)	M2 (M1 on request)
Reaction to fire / EUROCLASS classification (NF EN 13501-1 : 2018)	C-s1-d0
Emission COV	A+ French label
Care	gentle vacuuming every 3 to 5 months
Production	made in Paris

This data sheet cancels and replaces the previous ones. Please ensure that it is still valid. Any use or application of materials that does not comply with the rules set out in this document releases the manufacturer from all liability, including joint and several liability (art.1792-4 of the French Civil Code).

FabBRICK®

www.fab-brick.com
contact@fabbrick.fr

Update 10/2025